



Accessories

Fastlane[®] UL Recognized Power Supply

Energy efficiency for Fastlane turnstiles

Fastlane UL Recognized Power Supply provides localized power to Fastlane turnstiles while maintaining a high standard of environmental awareness.

Overview

The unit is designed for Fastlane optical turnstiles, and consists of a steel enclosure (black mild) housing up to four switched-mode power supply modules (UL File No. E333418). The power supply is available in one, two, or four-module units depending on the number of motorized pedestals in use. The correct quantity is shipped with the turnstiles.

Connections to the power supply unit (PSU) can be via direct conduit using either the metric or imperial apertures or cable glands provided.

Design

Fastlane turnstiles utilize remotely located power supplies to provide insulation from hazardous voltages. The PSU must not be fitted within a Fastlane pedestal. The PSU is designed to employ 60W 24V modules for each barrier drive system, ensuring that each module provides power to only one barrier system. The power supply is part of the leading Fastlane brand, and forms part of the turnstile CE marking assessments.

To comply with UL standards, the unit must:

- Be wall-mounted with cable entry from the top of the unit
- Be installed in a dry location, no exposure to liquid, vapor, or rain
 - Be connected one of two ways:
 - Permanently to the building wiring via a 16A protection device which is readily accessible
 - Via a power cord which must not be attached to any surface or run through walls, ceilings, or floors and positioned as close as possible to the socket outlet
- Have the PE terminal connected to a non-fused Earth

TECHNICAL SPECIFICATIONS

Dimensions	Connection to Fastlane	Cabling recommendation
<ul style="list-style-type: none"> ■ Length: 12.8" (325 mm) ■ Width: 7.8" (200 mm) ■ Height: 5.3" (136 mm) 	<ul style="list-style-type: none"> ■ Low voltage cables required to connect to Fastlane ■ Connection to CAT 5 Interface Board or Fastlane CPU card 	<ul style="list-style-type: none"> ■ 1.5 mm² cross sectional area for cable lengths of up to 50 ft (15 m)
Operating voltage	Current	Frequency
<ul style="list-style-type: none"> ■ 100 - 240 V AC 	<ul style="list-style-type: none"> ■ 5 A max 	<ul style="list-style-type: none"> ■ 50 - 60 H
Output	Fuse	Operating Temperature Range
<ul style="list-style-type: none"> ■ 24 V DC (25.5 V @ 2.4 A Max) per module 	<ul style="list-style-type: none"> ■ 5 amp time delay/ slow blow (UL recognized) 	<ul style="list-style-type: none"> ■ 14 °F - 104 °F (-10 °C - 40 °C)
Earth Connection	Certifications	
<ul style="list-style-type: none"> ■ Required (unfused) 	<ul style="list-style-type: none"> ■ UL 60950-1, 2nd edition CSA C22.2 No. 60950-1-07, 2nd edition 	

* Due to continuous improvements, specifications are subject to change without prior notice.